




ACO WEXEL - INSTALLATION DRAWING

ACO Polycrete Pty Ltd
Australia
Ph: 1300 765 226
www.acodrain.com.au

DRAWING NO. W-VSFD-1

FULL BODIED VERTICAL SHORT FLOOR DRAIN INSTALLED IN TILED FLOOR

ACO Limited
New Zealand
Ph: 0800 448 080
www.acodrain.co.nz



Please note: These details only provide a practical reference. ACO recommends designers and installers check local legislative standards and practices, or seek specialised engineering advice.

SPECIFICATION CLAUSE

ACO Wexel vertical short floor drain with height adjustable square Heelguard grates for tiled floor.

Specification

This floor drain shall be ACO Wexel vertical short floor drain with height adjustable square Heelguard grates - [insert type no. or part no.] for tiled floors.

Materials and design

The grate shall be finished stainless steel with M6 Hex socket screws; load rated to EN 1253 - *Gullies for buildings*; compliant to AS 3996 - *Access covers and grates* (Clause 3.3.5) for surface openings in pedestrian areas; AS 3996 (Clause 3.3.6) for bicycle tyre penetration resistance; ASME A112.6.3 (Section 7.12) compliant, American high heel Standard.

The grate assembly shall have a height adjustable provision to suit the finished floor level. The floor drain is available with an optional removable strainer for 100mm diameter pipe (part no. 141920).

The iron body shall have a nitrile rubber seal to allow push-in joint connection to suit PVC or HDPE pipe and a cast iron clamp ring with weep holes for waterproofing membrane secured with M6 Hex head bolt.